

BARCODE LABEL PRINTER CT200

4 Inch Desktop Barcode Printer

- CT200 barcode printer has the characteristics of long-term non-fading, friction resistance, high temperature resistance, etc. It has a wide range of applications in the field of marking.
- Two printing modes are available, the thermal transfer mode can print satin ribbon, coated paper, matte paper, water-washed PET, PVC and other materials. Thermal mode can print thermal labels or single sheets.
- Ultrafast printing speed & 203 DPI resolution.
- Max Printing Width 4.25" - Available for any label with width from 0.79" to 4.25".
- Interface: USB, Optional: Ethernet/RS-232/TF Card, Bluetooth



Optional Colors



Industry Logistics Commerce

- Support various consumables, easily print all kinds of wide-width industry labels.
- Adhered to the quality of the product dual motor design, good stability.
- Optional printing accessories (Guillotine cutting system with a peel-off sensor)

- Free Windows drivers and label design software (available via download).
- Provide Windows printer utility, Windows SDK and Android SDK.
- Less maintenance required with easy to replace auto-cutter, print head and platen rollers.
- Option Bluetooth support Android/iPhone.
- User-friendly clamshell design.
- Label capacity up to 127 mm (5 ")OD.
- Ribbon capacity up to 300 m.



Product Parameter

Model	CT200
Level	Professional
Printing Resolution	203dpi
Max Printing Speed	150mm/S (6"/S)
Max Printing Width	108mm
Max Printing Length	25m(100")
Label Length	10~2540mm (0.39" ~ 100")
Printing Method	Thermal Transfer & Direct Thermal
Max Printing Paper	115mm*Φ127mm
Ribbon Length	300m
Ribbon Width	110m
Products Size	326mm(W) * 228mm(H)*180mm(D)
Net Weight	2.7kg
Interface	<ul style="list-style-type: none">• USB• RS-232(Optional)• Ethernet(Optional)• Bluetooth(Optional)
Memory	64MB
Power	External universal switching power supply Input: AC 100-240V, 2.5A, 50-60Hz Power Switch, Eject Button LED, Indicator Light (3 Colors: Purple, Blue, Red)
Keys & Indicators	
Sensors	Head open sensor, Ribbon end sensor, Reflective sensor (moveable), Transmissive sensor(moveable)
1D Barcode	Code 39, Code 93, Code 128, Code 128M, EAN-8, EAN-13,UPC-A,UPC-E
2D Barcode	QR Code
Rotation	Font and barcode support 0, 90, 180, 270 degree
Printer Language	Compatible to TSPL,ZPL
Media Type	<ul style="list-style-type: none">• Continuous• Die-cut• Black mark,• Fan-fold (outside wound)• Linerless thermal label• Tag (perforated paper, satin ribbon)
Media Midth	<ul style="list-style-type: none">• 20 ~ 115mm (0.78" ~ 4.4")
Media Thickness	0.06~0.19mm (2.36 ~ 7.48 mil)
Media Core Diameter	25.4 mm (1")
Label Roll Capacity	127 mm (5") OD
Environment condition	<ul style="list-style-type: none">• Work environment: 5°C~40°C• Humidity: 25%~85%(non-condensation)• Storage environment: -40°C~60°C• Humidity: 10%~90%(non-condensation)
Safety Regulation	3C、FCC、CE、ROHS
Accessories	<ul style="list-style-type: none">• Quick start guide• USB cable• Power cord• Paper scroll• Paper stopper*2
Dealer Option System	Date/Time generator (RTC) Win XP/7/8/10, Mac 10.6

Industry Application



Logistics



Power Line Communication



Warehouse



Business



Washable Label



PET Silver Paper



Jewelry Label



Copper Plate Label



Shipping Label